



# 1106 Air - Water Hose



## DESCRIPTION

Cables are mostly unprotected.

Extremely flexible and resistant to torsion, cable protection hoses are used as a physical protection for flexible electric cables in applications such as robot joints and automatic welding machines.

They are manufactured with insulating rubber compounds, highly ageing- and ozone resistant, non-conductive and resisting chemicals and mineral oil.

Please contact Codan for further information.

## ADDITIONAL INFORMATION

Type no.	1106
Application	Air – water hose
Standard length	40 metres
Working temp.	-30°C to 80°C
Inside compound	EPDM
Inside colour	Black
Reinforcement	Polyester
Outside compound	EPDM
Outside colour	Black
Standards	–
Std. branding	–

Inside dia. (mm)	Outside dia. (mm)	Working Pressure BAR	Burst Pressure BAR	Bend Radius (mm)	Weight (g/m)	Product code
25,0	27,0	-	-	-	110	1106025000
32,0	34,0	-	-	-	150	1106032000
38,0	40,0	-	-	-	180	1106038000
600	62,0	-	-	-	280	1106060000

This hose specification sheet has been prepared with great care in order to provide you with all the information you need. The written advice must be obtained from Codan Rubber before using any hose with untested media or before using in applications not covered in the product data sheet. Codan Rubber recommends regular maintenance, care, and inspection of hoses before use. Hoses should be replaced if any physical damage is seen, especially to the cover of the hose or in the area around the couplings. All products must be stored in accordance with ISO 2230:2002 (Storage of vulcanized Rubber Products).

The individual conditions of an application will affect the lifetime of each product. Therefore please ensure that resistance to chemicals and cleaning procedures in our written product information is complied with. Codan Rubber's warranty is void in the event of misuse such as excessive bending, crushing, stretching, use with incorrect media or use in environments outside the hose specification. Please contact Codan Rubber for individual product manufacturing tolerances.