




1161 Steam Hose



DESCRIPTION

Mandrel built premium quality hose for use with saturated steam at temperatures up to 170°C, in paper mills, food industries and a wide range of industrial services. Ozone and weather resistant. Wrapped finish.

Contact Codan for further information.

ADDITIONAL INFORMATION

| | |
|-----------------|---------------------------------------|
| Type no. | 1161 |
| Application | Steam hose |
| Standard length | 40 metres |
| Working temp. | -25°C to 170°C |
| Inside compound | EPDM |
| Inside colour | Black |
| Reinforcement | High Strength Synthetic Textile Yarns |
| Outside colour | Black |
| Standards | – |
| Std. branding | – |

| Inside dia. (mm) | Outside dia. (mm) | Working Pressure BAR | Burst Pressure BAR | Bend Radius (mm) | Weight (g/m) | Product code |
|---------------------|----------------------|-------------------------|-----------------------|---------------------|-----------------|-----------------|
| 12,7 | 24,0 | 7 | 70 | 120 | 470 | 1161013000 |
| 19,0 | 32,0 | 7 | 70 | 190 | 580 | 1161019000 |
| 25,0 | 39,5 | 7 | 70 | 250 | 770 | 1161025000 |
| 32,0 | 47,0 | 7 | 70 | 320 | 980 | 1161032000 |
| 38,0 | 54,0 | 7 | 70 | 380 | 1170 | 1161038000 |
| 51,0 | 68,0 | 7 | 70 | 520 | 1570 | 1161051000 |

This hose specification sheet has been prepared with great care in order to provide you with all the information you need. The written advice must be obtained from Codan Rubber before using any hose with untested media or before using in applications not covered in the product data sheet. Codan Rubber recommends regular maintenance, care, and inspection of hoses before use. Hoses should be replaced if any physical damage is seen, especially to the cover of the hose or in the area around the couplings. All products must be stored in accordance with ISO 2230:2002 (Storage of vulcanized Rubber Products).

The individual conditions of an application will affect the lifetime of each product. Therefore please ensure that resistance to chemicals and cleaning procedures in our written product information is complied with. Codan Rubber's warranty is void in the event of misuse such as excessive bending, crushing, stretching, use with incorrect media or use in environments outside the hose specification. Please contact Codan Rubber for individual product manufacturing tolerances.