



1200 Air - Water Hose



DESCRIPTION

Antistatic mandrel built hose for transfer of water and other inert fluids. Specially developed by CODAN for fire hose reels. Protected with black NBR/PVC rubber with good weather resistant properties. Lined with foam resistant Black antistatic EPDM rubber.

Electrically conductive: $R < 10^6 \Omega/m$ (ISO 8031:2009).

Ozone resistant acc. DIN ISO 1431-1:2012-08.

Please contact Codan for further information.

ADDITIONAL INFORMATION

Type no.	1200
Application	Air – water hose
Standard length	30 metres
Working temp.	-40°C to 100°C
Inside compound	EPDM
Inside colour	Black
Reinforcement	High strength synthetic textile
Outside compound	NBR/PVC
Outside colour	Black
Standards	ISO 8031 + ISO 1431-1
Std. branding	–

Inside dia. (mm)	Outside dia. (mm)	Working Pressure BAR	Burst Pressure BAR	Bend Radius (mm)	Weight (g/m)	Product code
25,0	37,0	20	62	255	950	1200025000
32,0	45,0	20	62	300	1250	1200032000
38,0	51,0	20	62	350	1484	1200038000

This hose specification sheet has been prepared with great care in order to provide you with all the information you need. The written advice must be obtained from Codan Rubber before using any hose with untested media or before using in applications not covered in the product data sheet. Codan Rubber recommends regular maintenance, care, and inspection of hoses before use. Hoses should be replaced if any physical damage is seen, especially to the cover of the hose or in the area around the couplings. All products must be stored in accordance with ISO 2230:2002 (Storage of vulcanized Rubber Products).

The individual conditions of an application will affect the lifetime of each product. Therefore please ensure that resistance to chemicals and cleaning procedures in our written product information is complied with. Codan Rubber's warranty is void in the event of misuse such as excessive bending, crushing, stretching, use with incorrect media or use in environments outside the hose specification. Please contact Codan Rubber for individual product manufacturing tolerances.