

## 1206 Coolant Hose



۹

CODAN 1206 COOLANT HOSE - WP 20 BAR

## DESCRIPTION

Customer specified Black Hose, made specially with a cover for use in oil/greasy environments around moulding machines. The Liner ensures cooling of the moulding machine. The hose is outside smooth till/incl. 25mm and wrapped from 32mm and up- Length from 32mm is 40mtr. The indicated bend radius is an estimate, calculated on values for hoses without steel helix wire.

For further information please contact Codan.

## **ADDITIONAL INFORMATION**

**Type no.** 1206

**Application** Anti-freeze, Coolant hose, Glycol

**Standard length** 50 metres

**Working temp.** -30°C to 120°C

**Inside compound** EPDM

**Inside colour** Black

**Reinforcement** PFT

Outside compound NBR/PVC

Outside colour

Black

Standards

Std. branding

| Inside dia.<br>(mm) | Outside dia.<br>(mm) | Working Pressure<br>BAR | Burst Pressure<br>BAR | Bend Radius<br>(mm) | Weight<br>(g/m) | Product<br>code |
|---------------------|----------------------|-------------------------|-----------------------|---------------------|-----------------|-----------------|
| 12,5                | 21,0                 | 20                      | 60                    | 190                 | 300             | 1206013000      |
| 19,0                | 28,0                 | 20                      | 60                    | 220                 | 470             | 1206019000      |
| 25,0                | 36,0                 | 20                      | 60                    | 310                 | 660             | 1206025000      |
| 32,0                | 43,0                 | 12                      | 36                    | 390                 | 920             | 1206032000      |
| 38,0                | 51,0                 | 12                      | 36                    | 440                 | 1031            | 1206038000      |
| 50,0                | 65,0                 | 10                      | 30                    | 500                 | 1960            | 1206050000      |