



1220 Air - Water Hose



DESCRIPTION

Extremely sturdy and pliable hose for compressed air and water. Designed for heavy-duty work. High degree of resistance to impact and rough surfaces. Ideal for use in mines, quarries, tunnels, shipyards, etc.

Fits standard claw couplings in diameters less than 51 mm.

Please contact Codan for further information

ADDITIONAL INFORMATION

Type no.	1220
Application	Air – water hose
Standard length	40 metres
Working temp.	-30°C to 80°C
Inside compound	SBR/NR
Inside colour	Black
Reinforcement	Polyester
Outside compound	EPDM
Outside colour	Yellow
Standards	ISO 2398:2016, Type 2, Class B, Cat N-T

Inside dia. (mm)	Outside dia. (mm)	Working Pressure BAR	Burst Pressure BAR	Bend Radius (mm)	Weight (g/m)	Product code
13,0	22,6	20	64	120	500	1220013000
16,0	26,0	20	64	150	600	1220016000
19,0	29,4	20	64	180	670	1220019000
25,0	36,2	20	64	250	930	1220025000
32,0	45,6	20	64	320	1300	1220032000
38,0	51,6	20	64	350	1490	1220038000
45,0	59,4	20	64	450	1950	1220045000
51,0	65,4	20	64	500	2180	1220051000
63,0	77,0	20	64	600	2610	1220063000
76,0	91,6	20	64	900	3100	1220076000
90,0	106,0	20	64	1050	4700	1220090000
102,0	118,0	20	64	1150	5190	1220102000

This hose specification sheet has been prepared with great care in order to provide you with all the information you need. The written advice must be obtained from Codan Rubber before using any hose with untested media or before using in applications not covered in the product data sheet. Codan Rubber recommends regular maintenance, care, and inspection of hoses before use. Hoses should be replaced if any physical damage is seen, especially to the cover of the hose or in the area around the couplings. All products must be stored in accordance with ISO 2230:2002 (Storage of vulcanized Rubber Products).

The individual conditions of an application will affect the lifetime of each product. Therefore please ensure that resistance to chemicals and cleaning procedures in our written product information is complied with. Codan Rubber's warranty is void in the event of misuse such as excessive bending, crushing, stretching, use with incorrect media or use in environments outside the hose specification. Please contact Codan Rubber for individual product manufacturing tolerances.