



1232 Air - Water Hose



DESCRIPTION

Red, industrial-quality water hose for use in all types of industrial flushing, cleaning, etc. Hardwearing surface that also has excellent weather and ozone resistance.

From 32 mm: wrapped hose supplied in 40 m lengths. (old type 1210)
Working temp. -30°C to +80°C.
BP 3x safety factor. SBR/SBR.

Please contact Codan for further information.

ADDITIONAL INFORMATION

Application	Air – water hose
Standard length	50 metres
Working temp.	-30°C to 100°C
Inside compound	EPDM
Inside colour	Black
Reinforcement	Polyester
Outside compound	EPDM
Outside colour	Red
Standards	ISO 1403: 2019 type 2
Std. branding	–

Inside dia. (mm)	Outside dia. (mm)	Working Pressure BAR	Burst Pressure BAR	Bend Radius (mm)	Weight (g/m)	Product code
12,7	20,7	10	30	-	250	1232013000
15,9	23,9	10	30	-	330	1232016000
19,1	28,5	10	30	-	460	1232019000
20,6	29,0	10	30	-	465	1232021000
25,4	34,8	10	30	-	560	1232025000
32,0	42,0	10	30	-	880	1232032000
38,0	48,4	10	30	-	1020	1232038000
40,0	50,0	10	30	-	1100	1232040000
42,0	52,0	10	30	-	1150	1232052000
50,0	61,0	10	30	-	1360	1232050000
63,0	76,2	10	30	-	2100	1232063000
76,0	90,0	10	30	-	2740	1232076000
100,0	115,0	10	30	-	3690	1232100000
152,0	173,0	10	30	-	5870	1232152000

This hose specification sheet has been prepared with great care in order to provide you with all the information you need. The written advice must be obtained from Codan Rubber before using any hose with untested media or before using in applications not covered in the product data sheet. Codan Rubber recommends regular maintenance, care, and inspection of hoses before use. Hoses should be replaced if any physical damage is seen, especially to the cover of the hose or in the area around the couplings. All products must be stored in accordance with ISO 2230:2002 (Storage of vulcanized Rubber Products).

The individual conditions of an application will affect the lifetime of each product. Therefore please ensure that resistance to chemicals and cleaning procedures in our written product information is complied with. Codan Rubber's warranty is void in the event of misuse such as excessive bending, crushing, stretching, use with incorrect media or use in environments outside the hose specification. Please contact Codan Rubber for individual product manufacturing tolerances.