




1701 Material Handling Hose



DESCRIPTION

Black, flexible, wrapped pressure hose with strong, particularly hard-wearing inner lining which is anti-static. Discharge is also ensured by the anti-static wire incorporated in the hose. For various strongly abrasive materials, including dry cement, granulates, etc. Installed using special sand-blasting connectors.

Please contact Codan for further information.

ADDITIONAL INFORMATION

Type no.	1701
Application	Dry cement
Standard length	40 metres
Working temp.	-30°C to 80°C
Inside compound	NR
Inside colour	Black
Reinforcement	Polyester – Anti-static wire
Outside compound	EPDM/SBR
Outside colour	Black
Standards	–
Std. branding	–

Inside dia. (mm)	Outside dia. (mm)	Working BAR	Burst Pressure BAR	Bend Radius (mm)	Weight (g/m)	Product code
51,0	64,0	8	24	-	1470	1701051000
63,0	79,0	8	24	-	2660	1701063000
76,0	94,8	8	24	-	3240	1701076000
80,0	99,0	8	24	-	3430	1701080000
90,0	110,0	8	24	-	4050	1701090000
102,0	122,4	8	24	-	4520	1701102000
127,0	147,4	8	24	-	5520	1701127000
152,0	174,0	8	24	-	7180	1701152000
203,0	230,0	8	24	-	9660	1701203000

This hose specification sheet has been prepared with great care in order to provide you with all the information you need. The written advice must be obtained from Codan Rubber before using any hose with untested media or before using in applications not covered in the product data sheet. Codan Rubber recommends regular maintenance, care, and inspection of hoses before use. Hoses should be replaced if any physical damage is seen, especially to the cover of the hose or in the area around the couplings. All products must be stored in accordance with ISO 2230:2002 (Storage of vulcanized Rubber Products).

The individual conditions of an application will affect the lifetime of each product. Therefore please ensure that resistance to chemicals and cleaning procedures in our written product information is complied with. Codan Rubber's warranty is void in the event of misuse such as excessive bending, crushing, stretching, use with incorrect media or use in environments outside the hose specification. Please contact Codan Rubber for individual product manufacturing tolerances.