



1905 Bunker Hose



DESCRIPTION

Black, wrapped bunker hose with two charge eliminator wires to ensure complete discharge of static electricity.

For use in the oil industry, e.g. as unloading pipe from ship to quay, or for transporting mineral oil, fuel, etc. on ships.

Fits DIN clamps.

Max. 50% aromatics.

Please contact Codan for further information.

ADDITIONAL INFORMATION

Type no.	1905
Application	Bunker hose
Standard length	40 metres
Working temp.	-30°C to 70°C
Inside compound	NBR
Inside colour	Black
Reinforcement	Polyester
Outside compound	CR
Outside colour	Black
Standards	–
Std. branding	–

Inside dia. (mm)	Outside dia. (mm)	Working Pressure BAR	Burst Pressure BAR	Bend Radius (mm)	Weight (g/m)	Product code
51,0	62,0	16	48	-	1740	1905051000
76,0	90,4	16	48	-	2250	1905076000
102,0	116,8	16	48	-	3040	1905102000
127,0	142,2	16	48	-	3830	1905127000
152,0	169,6	16	48	-	5360	1905152000
203,0	224,2	16	48	-	8450	1905203000
254,0	275,6	16	48	-	10730	1905254000

This hose specification sheet has been prepared with great care in order to provide you with all the information you need. The written advice must be obtained from Codan Rubber before using any hose with untested media or before using in applications not covered in the product data sheet. Codan Rubber recommends regular maintenance, care, and inspection of hoses before use. Hoses should be replaced if any physical damage is seen, especially to the cover of the hose or in the area around the couplings. All products must be stored in accordance with ISO 2230:2002 (Storage of vulcanized Rubber Products).

The individual conditions of an application will affect the lifetime of each product. Therefore please ensure that resistance to chemicals and cleaning procedures in our written product information is complied with. Codan Rubber's warranty is void in the event of misuse such as excessive bending, crushing, stretching, use with incorrect media or use in environments outside the hose specification. Please contact Codan Rubber for individual product manufacturing tolerances.