



DESCRIPTION

Black, wrapped, flexible, industrial suction/pressure hose for air or water, with reinforcing steel helix. For use throughout industry, especially the building and construction sector, shipyards, etc.

Suitable for use with DIN clamps.
Max. vacuum: 90%.

Please contact Codan for further information.

ADDITIONAL INFORMATION

Type no.	2001
Application	Air – water hose
Standard length	40 metres
Working temp.	-30°C to 80°C
Inside compound	SBR
Inside colour	Black
Reinforcement	Polyester with steel helix
Outside compound	SBR
Outside colour	Black
Standards	
Std. branding	

Inside dia. (mm)	Outside dia. (mm)	Working Pressure BAR	Burst Pressure BAR	Bend Radius (mm)	Weight (g/m)	Product code
25,0	35,0	10	30	150	870	2001025000
32,0	42,0	10	30	180	1080	2001032000
38,0	49,2	10	30	310	1830	2001038000
51,0	62,0	10	30	310	1830	2001051000
63,0	75,0	10	30	380	2600	2001063000
76,0	88,8	10	30	460	3090	2001076000
90,0	104,0	10	30	535	3940	2001090000
102,0	117,2	10	30	620	4990	2001102000
127,0	143,4	10	30	880	7440	2001127000
152,0	168,8	10	30	1000	9270	2001152000
203,0	223,4	10	30	1200	13900	2001203000
254,0	280,4	10	30	1750	16550	2001254000

This hose specification sheet has been prepared with great care in order to provide you with all the information you need. The written advice must be obtained from Codan Rubber before using any hose with untested media or before using in applications not covered in the product data sheet. Codan Rubber recommends regular maintenance, care, and inspection of hoses before use. Hoses should be replaced if any physical damage is seen, especially to the cover of the hose or in the area around the couplings. All products must be stored in accordance with ISO 2230:2002 (Storage of vulcanized Rubber Products).

The individual conditions of an application will affect the lifetime of each product. Therefore please ensure that resistance to chemicals and cleaning procedures in our written product information is complied with. Codan Rubber's warranty is void in the event of misuse such as excessive bending, crushing, stretching, use with incorrect media or use in environments outside the hose specification. Please contact Codan Rubber for individual product manufacturing tolerances.