



2011 Pvc Hose



DESCRIPTION

Transparent, cadmium-free, non-reinforced PVC hose for air, water, certain chemicals, acids, oils, etc. under low pressure.

Transparent design allows effective flow control.

Normally installed using hose clamps.

Please contact Codan for further information.

ADDITIONAL INFORMATION

Type no.	2011
Application	PVC hose
Standard length	50 metres
Working temp.	-20°C to 55°C
Inside compound	PVC
Inside colour	Transparent
Reinforcement	–
Outside compound	–
Outside colour	Transparent
Standards	BGA/FDA
Std. branding	–

Inside dia. (mm)	Outside dia. (mm)	Working Pressure BAR	Burst Pressure BAR	Bend Radius (mm)	Weight (g/m)	Product code
3,0	6,0	-	-	50	15	2011003000
4,0	6,0	-	-	50	18	2011004000
5,0	8,0	-	-	65	26	2011005000
6,0	9,0	-	-	70	45	2011006000
8,0	11,0	-	-	85	57	2011008000
10,0	16,0	-	-	130	108	2011010000
12,0	15,0	-	-	120	138	2011012000
16,0	22,0	-	-	175	181	2011016000
19,0	25,0	-	-	200	231	2011019000
25,0	31,0	-	-	250	321	2011025000
32,0	38,0	-	-	300	411	2011032000
38,0	47,0	-	-	375	501	2011038000
50,0	62,0	-	-	495	681	2011050000

This hose specification sheet has been prepared with great care in order to provide you with all the information you need. The written advice must be obtained from Codan Rubber before using any hose with untested media or before using in applications not covered in the product data sheet. Codan Rubber recommends regular maintenance, care, and inspection of hoses before use. Hoses should be replaced if any physical damage is seen, especially to the cover of the hose or in the area around the couplings. All products must be stored in accordance with ISO 2230:2002 (Storage of vulcanized Rubber Products).

The individual conditions of an application will affect the lifetime of each product. Therefore please ensure that resistance to chemicals and cleaning procedures in our written product information is complied with. Codan Rubber's warranty is void in the event of misuse such as excessive bending, crushing, stretching, use with incorrect media or use in environments outside the hose specification. Please contact Codan Rubber for individual product manufacturing tolerances.