


2111 Pvc Hose



CODAN 2111 UNIVERSAL HOSE - WP 15 BAR

DESCRIPTION

Transparent, cadmium-free, reinforced PVC hose for air, water, certain chemicals, acids, oils, etc. under pressure. Polyester fabric liner provides stable working and bursting pressures and great flexibility. Transparent design allows effective flow control. Normally installed using hose clamps.

Please contact Codan for further information.

ADDITIONAL INFORMATION

Type no. 2111

Application PVC hose

Standard length 50 metres

Working temp. -20°C to 55°C

Inside compound PVC

Inside colourTransparentReinforcementPolyester

Outside compound

PVC

Outside colourTransparentStandardsBGA/FDA

Std. branding

Inside dia. (mm)	Outside dia. (mm)	Working Pressure BAR	Burst Pressure BAR	Bend Radius (mm)	Weight (g/m)	Product code
6,0	12,0	15	60	40	82	2111006000
8,0	14,0	15	60	65	113	2111008000
10,0	16,0	10	40	80	130	2111010000
12,5	18,5	10	40	100	166	2111013000
16,0	23,0	8	32	130	202	2111016000
19,0	27,0	7	28	150	285	2111019000
25,0	33,0	6	24	200	508	2111025000
32,0	42,0	6	22	255	413	2111032000
38,0	48,0	4	16	300	508	2111038000
50,0	60,0	3	12	400	698	2111050000

This hose specification sheet has been prepared with great care in order to provide you with all the information you need. The written advice must be obtained from Codan Rubber before using any hose with untested media or before using in applications not covered in the product data sheet. Codan Rubber recommends regular maintenance, care, and inspection of hoses before use. Hoses should be replaced if any physical damage is seen, especially to the cover of the hose or in the area around the couplings. All products must be stored in accordance with ISO 2230:2002 (Storage of vulcanized Rubber Products).

The individual conditions of an application will affect the lifetime of each product. Therefore please ensure that resistance to chemicals and cleaning procedures in our written product information is complied with. Codan Rubber's warranty is void in the event of misuse such as excessive bending, crushing, stretching, use with incorrect media or use in environments outside the hose specification. Please contact Codan Rubber for individual product manufacturing tolerances.