



DESCRIPTION

Transparent, cadmium-free, reinforced PVC hose for air, water, certain chemicals, acids, oils, etc. under pressure. Polyester fabric liner provides stable working and bursting pressures and great flexibility. Transparent design allows effective flow control.

Normally installed using hose clamps.

Please contact Codan for further information.

ADDITIONAL INFORMATION

Type no.	2111
Application	PVC hose
Standard length	50 metres
Working temp.	-20°C to 55°C
Inside compound	PVC
Inside colour	Transparent
Reinforcement	Polyester
Outside compound	PVC
Outside colour	Transparent
Standards	BGA/FDA
Std. branding	

Inside dia. (mm)	Outside dia. (mm)	Working Pressure BAR	Burst Pressure BAR	Bend Radius (mm)	Weight (g/m)	Product code
6,0	12,0	15	60	40	82	2111006000
8,0	14,0	15	60	65	113	2111008000
10,0	16,0	10	40	80	130	2111010000
12,5	18,5	10	40	100	166	2111013000
16,0	23,0	8	32	130	202	2111016000
19,0	27,0	7	28	150	285	2111019000
25,0	33,0	6	24	200	508	2111025000
32,0	42,0	6	22	255	413	2111032000
38,0	48,0	4	16	300	508	2111038000
50,0	60,0	3	12	400	698	2111050000