



2118 Air - Water Hose



DESCRIPTION

Extremely sturdy and pliable hose for compressed air and water. Smooth cover. Designed for heavy-duty work. High degree of resistance to impact and rough surfaces. Ideal for use in mines, quarries, tunnels, shipyards, etc. Fits standard claw couplings in diameters less than 51 mm.

Please contact Codan for further information.

ADDITIONAL INFORMATION

Type no.	2118
Application	Air – water hose
Standard length	–
Working temp.	-30°C to 90°C
Inside compound	SBR/NR
Inside colour	Black
Reinforcement	Polyester
Outside compound	EPDM
Outside colour	Yellow
Standards	ISO 2398:2016, Type 2, Class B, Cat N-T
Std. branding	–

Inside dia. (mm)	Outside dia. (mm)	Working Pressure BAR	Burst Pressure BAR	Bend Radius (mm)	Weight (g/m)	Product code
10,0	17,0	20	64	70	216	2118010000
12,5	22,5	20	64	150	350	2118013000
20,0	30,0	20	64	230	580	2118019000
25,5	36,0	20	64	300	750	2118025000

This hose specification sheet has been prepared with great care in order to provide you with all the information you need. The written advice must be obtained from Codan Rubber before using any hose with untested media or before using in applications not covered in the product data sheet. Codan Rubber recommends regular maintenance, care, and inspection of hoses before use. Hoses should be replaced if any physical damage is seen, especially to the cover of the hose or in the area around the couplings. All products must be stored in accordance with ISO 2230:2002 (Storage of vulcanized Rubber Products).

The individual conditions of an application will affect the lifetime of each product. Therefore please ensure that resistance to chemicals and cleaning procedures in our written product information is complied with. Codan Rubber's warranty is void in the event of misuse such as excessive bending, crushing, stretching, use with incorrect media or use in environments outside the hose specification. Please contact Codan Rubber for individual product manufacturing tolerances.