

## 2614 Gas Hose



CODAN 2614 GAS HOSE - PROPANE / BUTANE - EN16436-1

## **DESCRIPTION**

Flexible, smooth, orange hose for liquefied petroleum gas (LPG), propane/butane, to EN 16436-1 Class 2. The hose is primarily for use in assemblies of LPG applications.

For use with barbecues, patio heaters, caravan installations and weed burners.

The hose is DG-approved for sizes 6.3 - 10.0 Please contact Codan for further information.

Important: The European Committee For Standardization has introduced new standards for LPG hoses: EN16436-1 2014. Click here to read about the new regulations.

## **ADDITIONAL INFORMATION**

Type no.

**Application** LPG / Propane / Butane

**Standard length** 50 metres Working temp. -30°C to 80°C

Inside compound NBR **Inside colour** Black Reinforcement Polyester

Outside compound

**EPDM** 

**Outside colour** 

Orange

**Standards** EN 16436-1:2014+A3:2020 Class 2

Std. branding

Inside dia. (mm)	Outside dia. (mm)	Working Pressure BAR	Burst Pressure BAR	Bend Radius (mm)	Weight (g/m)	Product code
4,0	11,0	10	30	35	110	2614004000
5,0	12,0	10	30	40	125	2614005000
6,3	13,3	10	30	40	141	2614006000
8,0	15,0	10	30	45	173	2614008000
9,0	16,0	10	30	45	195	2614009000
10,0	20,0	10	30	50	216	2614010000
12,5	22,5	10	30	75	290	2614013000

This hose specification sheet has been prepared with great care in order to provide you with all the information you need. The written advice must be obtained from Codan Rubber before using any hose with untested media or before using in applications not covered in the product data sheet. Codan Rubber recommends regular maintenance, care, and inspection of hoses before use. Hoses should be replaced if any physical damage is seen, especially to the cover of the hose or in the area around the couplings. All products must be stored in accordance with ISO 2230:2002

The individual conditions of an application will affect the lifetime of each product. Therefore please ensure that resistance to chemicals and cleaning procedures in our written product information is complied with. Codan Rubber's warranty is void in the event of misuse such as excessive bending, crushing, stretching, use with incorrect media or use in environments outside the hose specification. Please contact Codan Rubber for individual product manufacturing tolerances.