



CODAN 2636 GAS HOSE - PROPANE / BUTANE - WP 18 BAR

DESCRIPTION

Orange, liquid-gas hose for butane and propane, to BS3212:1991 type 2. For use with gas-fuelled leisure appliances, e.g. barbecues and heaters.

CODAN

Please contact Codan for further information.

ADDITIONAL INFORMATION

Type no.	2636	
Application	LPG / Propane / Butane	
Standard length	50 metres	
Working temp.	-20°C to 80°C	
Inside compound	NBR	
Inside colour	Black	
Reinforcement	PVA	
Outside compound	CR	
Outside colour	Orange	
Standards	BS 3212: 1991 type 2	
Std. branding		

Inside dia. (mm)	Outside dia. (mm)	Working Pressure BAR	Burst Pressure BAR	Bend Radius (mm)	Weight (g/m)	Product code
4,0	10,4	18	52	36	106	2636004000
4,8	11,6	18	52	58	115	2636005000
6,3	13,1	18	52	65	137	2636006000
8,3	15,5	18	52	76	178	2636008000
9,5	17,3	18	52	60	239	2636010000
12,7	20,5	18	52	72	293	2636013000

The individual conditions of an application will affect the lifetime of each product. Therefore please ensure that resistance to chemicals and cleaning procedures in our written product information is complied with. Codan Rubber's warranty is void in the event of misuse such as excessive bending, crushing, stretching, use with incorrect media or use in environments outside the hose specification. Please contact Codan Rubber for individual product manufacturing tolerances.

This hose specification sheet has been prepared with great care in order to provide you with all the information you need. The written advice must be obtained from Codan Rubber before using any hose with untested media or before using in applications not covered in the product data sheet. Codan Rubber recommends regular maintenance, care, and inspection of hoses before use. Hoses should be replaced if any physical damage is seen, especially to the cover of the hose or in the area around the couplings. All products must be stored in accordance with ISO 2230:2002 (Storage of vulcanized Rubber Products).