



Black smooth rubber hose for low pressure LPG. Hose for transporting propane- butane gas in automotive applications. Please contact Codan for further information.

ADDITIONAL INFORMATION

Type no.	2658
Application	LPG / Propane / Butane
Standard length	50 metres
Working temp.	-25°C to 125°C
Inside compound	NBR
Inside colour	Black
Reinforcement	Polyester
Outside compound	EPDM
Outside colour	Black
Standards	–
Std. branding	–

Inside dia. (mm)	Outside dia. (mm)	Working Pressure BAR	Burst Pressure BAR	Bend Radius (mm)	Weight (g/m)	Product code
4,0	10,0	10	30	26	75	2658004000
5,0	11,0	10	30	32	94	2658005000
6,0	12,0	10	30	40	120	2658006000
10,0	17,0	10	30	58	192	2658010000
11,0	18,0	10	30	65	110	2658011000
12,0	19,0	10	30	70	230	2658012000
14,0	22,0	10	30	90	350	2658014000
16,0	24,0	30	10	110	450	2658016000
19,0	28,0	30	10	113	530	2658019000

This hose specification sheet has been prepared with great care in order to provide you with all the information you need. The written advice must be obtained from Codan Rubber before using any hose with untested media or before using in applications not covered in the product data sheet. Codan Rubber recommends regular maintenance, care, and inspection of hoses before use. Hoses should be replaced if any physical damage is seen, especially to the cover of the hose or in the area around the couplings. All products must be stored in accordance with ISO 2230:2002 (Storage of vulcanized Rubber Products).

© Codan Rubber Danmark A/S Valdemarshaab 1, DK-4600 Køge, Denmark
Tel. +45 56 64 64 Fax +45 56 64 65 48 Mail: info@codan.com www.codan.com

The individual conditions of an application will affect the lifetime of each product. Therefore please ensure that resistance to chemicals and cleaning procedures in our written product information is complied with. Codan Rubber's warranty is void in the event of misuse such as excessive bending, crushing, stretching, use with incorrect media or use in environments outside the hose specification. Please contact Codan Rubber for individual product manufacturing tolerances.