



Black, wrapped suction/pressure hose with strong, smooth, hard-wearing inner lining which is anti-static. For vacuuming sand, dry cement and other strongly abrasive materials. Please contact Codan for further information.

ADDITIONAL INFORMATION

Type no.	2700
Application	Abrasive materials – suction
Standard length	40 metres
Working temp.	-30°C to 70°C
Inside compound	NR
Inside colour	Black
Reinforcement	Polyester w/ double steel helix
Outside compound	SBR
Outside colour	Black
Standards	–
Std. branding	–

Inside dia. (mm)	Outside dia. (mm)	Working BAR	Burst Pressure BAR	Bend Radius (mm)	Weight (g/m)	Product code
51,0	65,0	5	15	310	1900	2700051000
63,5	78,0	5	15	380	2700	2700063000
76,0	91,0	5	15	460	3100	2700076000
80,0	96,0	5	15	500	3450	2700080000
90,0	106,0	5	15	550	3900	2700090000
102,0	118,0	5	15	610	4500	2700102000
110,0	128,0	5	15	690	5200	2700110000
127,0	145,0	5	15	760	6180	2700127000
152,0	172,0	4	12	910	8800	2700152000
203,0	223,0	3	9	1250	11900	2700203000
254,0	279,0	3	9	1800	17950	2700254000

This hose specification sheet has been prepared with great care in order to provide you with all the information you need. The written advice must be obtained from Codan Rubber before using any hose with untested media or before using in applications not covered in the product data sheet. Codan Rubber recommends regular maintenance, care, and inspection of hoses before use. Hoses should be replaced if any physical damage is seen, especially to the cover of the hose or in the area around the couplings. All products must be stored in accordance with ISO 2230:2002 (Storage of vulcanized Rubber Products).

© Codan Rubber Danmark A/S Valdemarshaab 1, DK-4600 Køge, Denmark
Tel. +45 56 64 64 Fax +45 56 64 65 48 Mail: info@codan.com www.codan.com

The individual conditions of an application will affect the lifetime of each product. Therefore please ensure that resistance to chemicals and cleaning procedures in our written product information is complied with. Codan Rubber's warranty is void in the event of misuse such as excessive bending, crushing, stretching, use with incorrect media or use in environments outside the hose specification. Please contact Codan Rubber for individual product manufacturing tolerances.