



2715 Material Handling Hose



DESCRIPTION

An easy and flexible suction hose with high wearability. Black and corrugated surface.

90% Vacuum.

Lengths: up to 4" - 40 m; 127 and 152 mm – 25 m; 203 mm – 20 m.

Please contact Codan for further information.

ADDITIONAL INFORMATION

Type no.	2710
Application	Material handling hose
Standard length	–
Working temp.	-40°C to 80°C
Inside compound	Natural Rubber
Inside colour	Black
Reinforcement	Synthetic Textile yarns and steel spiral
Outside compound	SBR
Outside colour	Black
Standards	–
Std. branding	–

Inside dia. (mm)	Outside dia. (mm)	Working BAR	Burst Pressure BAR	Bend Radius (mm)	Weight (g/m)	Product code
51,0	65,0	10	30	150	1650	2715051000
64,0	77,0	10	30	220	2210	2715063000
76,0	90,0	10	30	300	2510	2715076000
102,0	116,0	10	30	350	3510	2715102000
110,0	126,0	10	30	150	4010	2715110000
127,0	143,0	5	15	550	5220	2715127000
152,0	168,0	5	15	600	6240	2715152000

This hose specification sheet has been prepared with great care in order to provide you with all the information you need. The written advice must be obtained from Codan Rubber before using any hose with untested media or before using in applications not covered in the product data sheet. Codan Rubber recommends regular maintenance, care, and inspection of hoses before use. Hoses should be replaced if any physical damage is seen, especially to the cover of the hose or in the area around the couplings. All products must be stored in accordance with ISO 2230:2002 (Storage of vulcanized Rubber Products).

The individual conditions of an application will affect the lifetime of each product. Therefore please ensure that resistance to chemicals and cleaning procedures in our written product information is complied with. Codan Rubber's warranty is void in the event of misuse such as excessive bending, crushing, stretching, use with incorrect media or use in environments outside the hose specification. Please contact Codan Rubber for individual product manufacturing tolerances.