



# 2710 Material Handling Hose



## DESCRIPTION

An easy and flexible suction hose with high wearability. Black and corrugated surface.

90% Vacuum.

Lengths: up to 4" - 40 m; 127 and 152 mm – 25 m; 203 mm – 20 m.

Please contact Codan for further information.

## ADDITIONAL INFORMATION

Type no.	2710
Application	Abrasive materials – suction
Standard length	–
Working temp.	-40°C to 80°C
Inside compound	Natural Rubber
Inside colour	Brown
Reinforcement	Synthetic Textile yarns and steel spiral
Outside compound	NR/SBR
Outside colour	Black
Standards	–
Std. branding	–

Inside dia. (mm)	Outside dia. (mm)	Working BAR	Burst Pressure BAR	Bend Radius (mm)	Weight (g/m)	Product code
40,0	51,0	-	-	-	830	2710040000
50,0	61,0	-	-	-	1150	2710050000
63,0	76,0	-	-	-	1430	2710063000
76,0	89,0	-	-	-	1740	2710076000
90,0	104,0	-	-	-	2450	2710090000
102,0	116,0	-	-	-	2950	2710102000
127,0	144,0	-	-	-	3600	2710127000
152,0	169,0	-	-	370	4400	2710152000
203,0	220,0	-	-	610	8230	2710203000

This hose specification sheet has been prepared with great care in order to provide you with all the information you need. The written advice must be obtained from Codan Rubber before using any hose with untested media or before using in applications not covered in the product data sheet. Codan Rubber recommends regular maintenance, care, and inspection of hoses before use. Hoses should be replaced if any physical damage is seen, especially to the cover of the hose or in the area around the couplings. All products must be stored in accordance with ISO 2230:2002 (Storage of vulcanized Rubber Products).

The individual conditions of an application will affect the lifetime of each product. Therefore please ensure that resistance to chemicals and cleaning procedures in our written product information is complied with. Codan Rubber's warranty is void in the event of misuse such as excessive bending, crushing, stretching, use with incorrect media or use in environments outside the hose specification. Please contact Codan Rubber for individual product manufacturing tolerances.