



## DESCRIPTION

Flexible twin hose for propane/butane and oxygen. Dividing groove allows easy separation.

Specially designed for industrial cutting and welding tasks.

Normally installed using hose clamps or swaged on fittings.

Please contact Codan for further information.

## ADDITIONAL INFORMATION

<b>Type no.</b>	2808
<b>Application</b>	Oxygen / LPG (Propane / Butane)
<b>Standard length</b>	50 metres
<b>Working temp.</b>	-25°C to 80°C
<b>Inside compound</b>	NBR
<b>Inside colour</b>	Black
<b>Reinforcement</b>	PVA
<b>Outside compound</b>	SBR
<b>Outside colour</b>	Blue/Orange
<b>Standards</b>	EN ISO 3821:2019
<b>Std. branding</b>	

Inside dia. (mm)	Outside dia. (mm)	Working Pressure BAR	Burst Pressure BAR	Bend Radius (mm)	Weight (g/m)	Product code
5,0 / 5,0	11,0	20	60	50	300	2808505000
6,3 / 6,3	12,0	20	60	60	350	2808606000
6,3 / 8,0	16,0	20	80	80	400	2808608000
6,0 / 9,0	16,0	20	60	90	500	2808609000
10,0 / 10,0	17,0	20	60	100	760	2808909000