



DESCRIPTION

Lightweight, flexible, blue welding hose. The ribbed surface allows the hose to be dragged easily across the floor and prevents it becoming dirty. For transporting oxygen in autogenic welding equipment used in industrial plant, shipyards, building sites, etc. As it is lightweight, the hose is also ideal for compressed air. Also available in 100 m lengths. Normally installed using hose clamps and specially designed brass fittings. Note! Crimped-on fittings are recommended.

Please contact Codan for further information.

ADDITIONAL INFORMATION

Type no.	2812
Application	Oxygen
Standard length	50 metres
Working temp.	-40°C to 100°C
Inside compound	EPDM
Inside colour	Black
Reinforcement	Polyester
Outside compound	EPDM
Outside colour	Blue
Standards	EN ISO 3821: 2019
Std. branding	

Inside dia. (mm)	Outside dia. (mm)	Working Pressure BAR	Burst Pressure BAR	Bend Radius (mm)	Weight (g/m)	Product code
5,0	11,4	20	60	50	110	2812005000
6,3	12,9	20	60	63	140	2812006000
8,0	14,8	20	60	80	165	2812008000
9,5	16,5	20	60	100	210	2812010000
12,7	19,7	20	60	110	260	2812013000
15,9	26,9	20	60	180	560	2812016000
19,1	30,1	20	60	190	640	2812019000
25,4	36,4	20	60	210	795	2812025000