



# 2901 Oil Hose



## DESCRIPTION

Black, flexible, wrapped suction and pressure hose for oil and petrol, with double steel helix and anti-static wire.

Ideal for mineral oils, e.g. grease, oil and paraffin, and leaded or unleaded petrol. Max. 50% aromatics. The extremely hard-wearing, weather and ozone-resistant outer rubber coating ensures long service life.

Vacuum: Decreasing 90-40%.

Suitable for use with DIN clamps.

Please contact Codan for further information.

## ADDITIONAL INFORMATION

Type no.	2901
Application	Oil/Fuel
Standard length	40 metres
Working temp.	-40°C to 70°C
Inside compound	NBR
Inside colour	Black
Reinforcement	Polyester w/ double steel helix and anti-static wire
Outside compound	CR
Outside colour	Black
Standards	EN 1761:1999, EN12115:2021 Type SD

Inside dia. (mm)	Outside dia. (mm)	Working BAR	Burst Pressure BAR	Bend Radius (mm)	Weight (g/m)	Product code
25,0	35,0	10	30	150	790	2901025000
32,0	42,0	10	30	160	1010	2901032000
38,0	49,0	10	30	210	1280	2901038000
45,0	57,0	10	30	250	1460	2901045000
51,0	63,0	10	30	280	1720	2901051000
57,0	71,4	10	30	315	2295	2901057000
60,0	74,4	10	30	330	2300	2901060000
63,0	78,6	10	30	340	2750	2901063000
76,0	91,0	10	30	420	3215	2901076000
90,0	106,0	10	30	530	3800	2901090000
102,0	118,0	10	30	610	4875	2901102000
127,0	146,0	10	30	715	6710	2901127000
152,0	171,0	10	30	910	10140	2901152000

This hose specification sheet has been prepared with great care in order to provide you with all the information you need. The written advice must be obtained from Codan Rubber before using any hose with untested media or before using in applications not covered in the product data sheet. Codan Rubber recommends regular maintenance, care, and inspection of hoses before use. Hoses should be replaced if any physical damage is seen, especially to the cover of the hose or in the area around the couplings. All products must be stored in accordance with ISO 2230:2002 (Storage of vulcanized Rubber Products).

The individual conditions of an application will affect the lifetime of each product. Therefore please ensure that resistance to chemicals and cleaning procedures in our written product information is complied with. Codan Rubber's warranty is void in the event of misuse such as excessive bending, crushing, stretching, use with incorrect media or use in environments outside the hose specification. Please contact Codan Rubber for individual product manufacturing tolerances.