



2903 Fuel Hose



DESCRIPTION

Lightweight, flexible, corrugated suction and pressure hose for oil and leaded or unleaded petrol.

Max. 50% aromatics.

Vacuum: 90%.

Supplied with steel helix and charge eliminator wire.

Please contact Codan for further information.

ADDITIONAL INFORMATION

Type no.	2903
Application	Fuel hose, Oil hose
Standard length	40 metres
Working temp.	-30°C to 100°C
Inside compound	NBR
Inside colour	Black
Reinforcement	Polyester w/ double steel helix and anti-static wire
Outside compound	CR
Outside colour	Black
Standards	—
Std. branding	—

Inside dia. (mm)	Outside dia. (mm)	Working Pressure BAR	Burst Pressure BAR	Bend Radius (mm)	Weight (g/m)	Product code
51,0	63,0	5	15	150	1770	2903051000
76,0	88,0	5	15	200	2120	2903076000
102,0	115,0	5	15	250	3550	2903102000

This hose specification sheet has been prepared with great care in order to provide you with all the information you need. The written advice must be obtained from Codan Rubber before using any hose with untested media or before using in applications not covered in the product data sheet. Codan Rubber recommends regular maintenance, care, and inspection of hoses before use. Hoses should be replaced if any physical damage is seen, especially to the cover of the hose or in the area around the couplings. All products must be stored in accordance with ISO 2230:2002 (Storage of vulcanized Rubber Products).

The individual conditions of an application will affect the lifetime of each product. Therefore please ensure that resistance to chemicals and cleaning procedures in our written product information is complied with. Codan Rubber's warranty is void in the event of misuse such as excessive bending, crushing, stretching, use with incorrect media or use in environments outside the hose specification. Please contact Codan Rubber for individual product manufacturing tolerances.