



2915 Oil Hose



DESCRIPTION

Black, heavy-duty, wrapped suction and pressure hose for oil and petrol, with double steel helix and anti-static wire.

Ideal for mineral oils, e.g. grease, oil and paraffin, and leaded or unleaded petrol. Max. 50% aromatics. The extremely hard-wearing, weather and ozone-resistant outer rubber coating ensures long service life.

Vacuum: Decreasing 90-40%.

Suitable for use with reusable DIN clamps.

Please contact Codan for further information.

ADDITIONAL INFORMATION

Type no.	2915
Application	Oil/Fuel
Standard length	40 metres
Working temp.	-30°C to 100°C
Inside compound	NBR
Inside colour	Black
Reinforcement	Polyester w/ double steel helix and anti-static wire
Outside compound	CR
Outside colour	Black
Standards	EN 1761:1999, EN12115:2021 Type SD
Std. branding	2915 OIL/FUEL – EN12115 – NBR1 – SD – M – EN1761 – 16BAR

Inside dia. (mm)	Outside dia. (mm)	Working BAR	Burst Pressure BAR	Bend Radius (mm)	Weight (g/m)	Product code
25,0	36,0	16	48	150	900	2915025000
32,0	44,0	16	48	175	1120	2915032000
38,0	51,2	16	48	225	1375	2915038000
40,0	53,0	16	48	230	1425	2915040000
45,0	57,0	16	48	250	1720	2915045000
51,0	65,0	16	48	275	1900	2915051000
63,0	79,0	16	48	300	2880	2915063000
76,0	91,0	16	48	350	3380	2915076000
80,0	96,0	16	48	360	3870	2915080000
90,0	107,2	16	48	410	4290	2915090000
102,0	121,0	16	48	450	5370	2915102000
127,0	147,0	16	48	570	7820	2915127000
152,0	172,0	16	48	685	10240	2915152000
203,0	228,0	16	48	920	14390	2915203000

This hose specification sheet has been prepared with great care in order to provide you with all the information you need. The written advice must be obtained from Codan Rubber before using any hose with untested media or before using in applications not covered in the product data sheet. Codan Rubber recommends regular maintenance, care, and inspection of hoses before use. Hoses should be replaced if any physical damage is seen, especially to the cover of the hose or in the area around the couplings. All products must be stored in accordance with ISO 2230:2002 (Storage of vulcanized Rubber Products).

The individual conditions of an application will affect the lifetime of each product. Therefore please ensure that resistance to chemicals and cleaning procedures in our written product information is complied with. Codan Rubber's warranty is void in the event of misuse such as excessive bending, crushing, stretching, use with incorrect media or use in environments outside the hose specification. Please contact Codan Rubber for individual product manufacturing tolerances.