



3014 Oil Hose



DESCRIPTION

Long length oil hose for transfer and delivery of mineral oils, greases and petroleum based products up to a maximum aromatic content of 50%. Electrically conductive: $R < 10^6 \text{ Ohm/m}$ (ISO 8031:2009).

ADDITIONAL INFORMATION

Type no.	3014
Application	Oil / Grease / Universal
Standard length	50 metres
Working temp.	-40°C to 100°C
Inside compound	NBR
Inside colour	Black
Reinforcement	PVA
Outside compound	NBR/PVC
Outside colour	Black
Standards	EN228:2004, EN 590: 2004
Std. branding	–

Inside dia. (mm)	Outside dia. (mm)	Working BAR	Burst Pressure BAR	Bend Radius (mm)	Weight (g/m)	Product code
6,0	12,0	10	40	45	150	3014006000
8,0	14,0	10	40	55	120	3014008000
10,0	17,0	10	40	60	170	3014010000
13,0	20,0	10	40	80	240	3014013000
16,0	24,0	10	40	100	330	3014016000
19,0	28,0	10	40	120	430	3014019000
22,0	31,0	10	40	132	500	3014022000
25,0	35,0	10	40	150	620	3014025000

This hose specification sheet has been prepared with great care in order to provide you with all the information you need. The written advice must be obtained from Codan Rubber before using any hose with untested media or before using in applications not covered in the product data sheet. Codan Rubber recommends regular maintenance, care, and inspection of hoses before use. Hoses should be replaced if any physical damage is seen, especially to the cover of the hose or in the area around the couplings. All products must be stored in accordance with ISO 2230:2002 (Storage of vulcanized Rubber Products).

The individual conditions of an application will affect the lifetime of each product. Therefore please ensure that resistance to chemicals and cleaning procedures in our written product information is complied with. Codan Rubber's warranty is void in the event of misuse such as excessive bending, crushing, stretching, use with incorrect media or use in environments outside the hose specification. Please contact Codan Rubber for individual product manufacturing tolerances.