

3015 Oil Hose



CODAN 3015 OILFLOW HOSE - WP 15 BAR

DESCRIPTION

New improved version of our Codan 3009. Improved inner liner with better oil/diesel resistance. Flexible universal hose for industrial applications. Usable for Agri diesel pumps, on reels, in workshops etc. Dirt-repellent outer cover with good ozone and weather resistance. Cover ensures good coil-up on reels. PET Yarn with high drag force makes the hose strong pulling in the longitudinal direction. Normally fitted using hose clamps or crimped ferrules.

Please contact Codan for further information.

ADDITIONAL INFORMATION

Type no. 3015

Application 0il hose

Standard length 50 metres

Working temp. -30°C to 100°C

Inside compoundNBRInside colourBlackReinforcementPET

Outside compound NBR/PVC

Outside colour Black

Standards Codan 3015 – 'Dim' – Oil Flow – 15

BAR WP – batchno.

Std. branding

Inside dia. (mm)	Outside dia. (mm)	Working BAR	Burst Pressure BAR	Bend Radius (mm)	Weight (g/m)	Product code
19,1	27,0	15	45	95	433	3015019000
25,4	34,4	15	45	125	561	3015025000

This hose specification sheet has been prepared with great care in order to provide you with all the information you need. The written advice must be obtained from Codan Rubber before using any hose with untested media or before using in applications not covered in the product data sheet. Codan Rubber recommends regular maintenance, care, and inspection of hoses before use. Hoses should be replaced if any physical damage is seen, especially to the cover of the hose or in the area around the couplings. All products must be stored in accordance with ISO 2230:2002 (Storage of vulcanized Rubber Products).

The individual conditions of an application will affect the lifetime of each product. Therefore please ensure that resistance to chemicals and cleaning procedures in our written product information is complied with. Codan Rubber's warranty is void in the event of misuse such as excessive bending, crushing, stretching, use with incorrect media or use in environments outside the hose specification. Please contact Codan Rubber for individual product manufacturing tolerances.