



3020 Oil Hose



DESCRIPTION

Black, flexible pressure hose for oil, water and air.
Universal hose for industrial applications.
Dirt-repellent outer coating and good ozone and weather resistance.
Normally installed using hose clamps or screw couplings.

Please contact Codan for further information.

ADDITIONAL INFORMATION

Type no.	3020
Application	Oil / Grease / Universal
Standard length	50 metres
Working temp.	-30°C to 100°C
Inside compound	NBR
Inside colour	Black
Reinforcement	–
Outside compound	NBR/PVC
Outside colour	Black
Standards	–
Std. branding	–

Inside dia. (mm)	Outside dia. (mm)	Working BAR	Burst Pressure BAR	Bend Radius (mm)	Weight (g/m)	Product code
10,0	16,4	20	60	55	200	3020010000
13,0	19,6	20	60	70	260	3020013000
19,1	27,0	20	60	100	450	3020019000
25,4	34,4	30	60	135	570	3020025000

This hose specification sheet has been prepared with great care in order to provide you with all the information you need. The written advice must be obtained from Codan Rubber before using any hose with untested media or before using in applications not covered in the product data sheet. Codan Rubber recommends regular maintenance, care, and inspection of hoses before use. Hoses should be replaced if any physical damage is seen, especially to the cover of the hose or in the area around the couplings. All products must be stored in accordance with ISO 2230:2002 (Storage of vulcanized Rubber Products).

The individual conditions of an application will affect the lifetime of each product. Therefore please ensure that resistance to chemicals and cleaning procedures in our written product information is complied with. Codan Rubber's warranty is void in the event of misuse such as excessive bending, crushing, stretching, use with incorrect media or use in environments outside the hose specification. Please contact Codan Rubber for individual product manufacturing tolerances.