



3111 Fuel Hose



DESCRIPTION

Flexible, black hose for leaded and unleaded petrol, to SAE 30 R6.
Good ozone resistance. Resistant to oil spray in engine compartments.
For fuel pipes in cars, lorries, lawn mowers, garden cultivators, etc.
Acc. EN228:2008 and EN590:2010

Please contact Codan for further information.

ADDITIONAL INFORMATION

Type no.	3111
Application	Diesel, Fuel hose
Standard length	50 metres
Working temp.	-30°C to 100°C
Inside compound	NBR
Inside colour	Black
Reinforcement	PVA
Outside compound	CR
Outside colour	Black
Standards	SAE J30 R6 – 2022
Std. branding	–

Inside dia. (mm)	Outside dia. (mm)	Working Pressure BAR	Burst Pressure BAR	Bend Radius (mm)	Weight (g/m)	Product code
3,2	9,2	10	50	15	95	3111032000
3,5	9,5	10	50	15	98	3111035000
4,0	10,0	10	50	15	100	3111040000
4,8	10,8	10	50	15	110	3111048000
5,0	11,0	10	50	20	120	3111050000
5,5	11,5	10	50	20	125	3111055000
6,0	12,0	10	50	20	130	3111060000
6,3	12,7	10	50	20	130	3106065000
7,9	14,4	10	50	45	160	3111079000
8,0	14,0	10	50	25	180	3111080000
9,5	16,7	10	50	40	200	3111095000
10,0	17,0	10	60	40	230	3111100000
11,0	18,2	10	50	45	250	3111110000
12,7	19,7	10	50	50	257	3111127000
13,0	20,0	10	50	50	270	3111130000
16,0	24,0	10	50	80	320	3111160000

This hose specification sheet has been prepared with great care in order to provide you with all the information you need. The written advice must be obtained from Codan Rubber before using any hose with untested media or before using in applications not covered in the product data sheet. Codan Rubber recommends regular maintenance, care, and inspection of hoses before use. Hoses should be replaced if any physical damage is seen, especially to the cover of the hose or in the area around the couplings. All products must be stored in accordance with ISO 2230:2002 (Storage of vulcanized Rubber Products).

The individual conditions of an application will affect the lifetime of each product. Therefore please ensure that resistance to chemicals and cleaning procedures in our written product information is complied with. Codan Rubber's warranty is void in the event of misuse such as excessive bending, crushing, stretching, use with incorrect media or use in environments outside the hose specification. Please contact Codan Rubber for individual product manufacturing tolerances.