



3122 Fuel Hose



DESCRIPTION

Flexible, black hose for leaded and unleaded petrol. Good ozone resistance. Resistant to oil spray in engine compartments. For fuel pipes in cars, lorries, lawn mowers, garden cultivators, etc. The hose is based on SAE J30 R6, R7, R8, R11 [1998]
Acc. EN228:2008 and EN590:2010.

Please contact Codan for further information.

ADDITIONAL INFORMATION

Type no.	3122
Application	Diesel, Fuel hose
Standard length	50 metres
Working temp.	-40°C to 135°C
Inside compound	NBR
Inside colour	Black
Reinforcement	Polyester
Outside compound	CPE
Outside colour	Black
Standards	SAE J30 R6,R7, R8, R11 – 2022
Std. branding	–

Inside dia. (mm)	Outside dia. (mm)	Working BAR	Burst Pressure BAR	Bend Radius (mm)	Weight (g/m)	Product code
4,0	10,8	5	50	33	111	3122004000
4,8	11,6	5	50	35	122	3122005000
5,6	12,6	5	50	37	140	3122005600
6,3	13,3	5	50	40	150	3122006000
7,6	14,6	5	50	43	170	3122008000
9,5	16,5	5	50	49	198	3122010000
11,5	18,5	5	50	55	223	3122011500
12,0	19,0	5	50	57	236	3122012000

This hose specification sheet has been prepared with great care in order to provide you with all the information you need. The written advice must be obtained from Codan Rubber before using any hose with untested media or before using in applications not covered in the product data sheet. Codan Rubber recommends regular maintenance, care, and inspection of hoses before use. Hoses should be replaced if any physical damage is seen, especially to the cover of the hose or in the area around the couplings. All products must be stored in accordance with ISO 2230:2002 (Storage of vulcanized Rubber Products).

The individual conditions of an application will affect the lifetime of each product. Therefore please ensure that resistance to chemicals and cleaning procedures in our written product information is complied with. Codan Rubber's warranty is void in the event of misuse such as excessive bending, crushing, stretching, use with incorrect media or use in environments outside the hose specification. Please contact Codan Rubber for individual product manufacturing tolerances.