



3133 Fuel Hose



DESCRIPTION

Black, Zincfree and flexible hose for fuel in automotive or engine application. High resistance to all above media and especially used in Car, Truck, Agricultural and Construction equipment vehicles for fuel injection systems. High temp hose with low permeation for Petrol at less than 15g/m²/24hrs. Normally installed using crimped ferrules or petrol hose clips.

Suitable for petrol, diesel, ethanol, gasoline, oxidized sour gas, oil and biodiesel.

Intermittent Temperature: +150 °C

Please contact Codan for further information.

ADDITIONAL INFORMATION

Type no.	3133
Application	Bio-diesel, Diesel, Fuel hose
Standard length	25 metres
Working temp.	-30°C to 130°C
Inside compound	FKM/NBR
Inside colour	Black
Reinforcement	PVA
Outside compound	CSM
Outside colour	Black
Standards	SAE J30 R9 – 2022
Std. branding	–

Inside dia. (mm)	Outside dia. (mm)	Working BAR	Burst Pressure BAR	Bend Radius (mm)	Weight (g/m)	Product code
4,8	11,8	10	62	46	195	3133048000
5,6	12,0	10	62	52	130	3133056000
6,0	12,0	10	62	55	140	3133060000
6,3	12,7	10	62	56	150	3133063000
7,3	13,3	7	62	60	165	3133073000
7,9	14,5	7	62	58	180	3133071000
9,5	16,5	7	62	62	230	3133095000
12,0	19,0	7	34	65	240	3133120000
12,7	19,9	7	34	68	250	3133127000
15,6	22,4	7	34	76	271	3133156000

This hose specification sheet has been prepared with great care in order to provide you with all the information you need. The written advice must be obtained from Codan Rubber before using any hose with untested media or before using in applications not covered in the product data sheet. Codan Rubber recommends regular maintenance, care, and inspection of hoses before use. Hoses should be replaced if any physical damage is seen, especially to the cover of the hose or in the area around the couplings. All products must be stored in accordance with ISO 2230:2002 (Storage of vulcanized Rubber Products).

The individual conditions of an application will affect the lifetime of each product. Therefore please ensure that resistance to chemicals and cleaning procedures in our written product information is complied with. Codan Rubber's warranty is void in the event of misuse such as excessive bending, crushing, stretching, use with incorrect media or use in environments outside the hose specification. Please contact Codan Rubber for individual product manufacturing tolerances.