



## DESCRIPTION

Black, Zincfree and flexible hose for fuel in automotive or engine application. High resistance to all above media and especially used in Car, Truck, Agricultural and Construction equipment vehicles for fuel injection systems. High temp hose with low permeation for Petrol at less than 15g/m<sup>3</sup>/24hrs. Normally installed using crimped ferrules or petrol hose clips.

Suitable for petrol, diesel, ethanol, gasoline, oxidized sour gas, oil and biodiesel.

Intermittent Temperature: +150 °C

Please contact Codan for further information.

## ADDITIONAL INFORMATION

<b>Type no.</b>	3133
<b>Application</b>	Bio-diesel, Diesel, Fuel hose
<b>Standard length</b>	25 metres
<b>Working temp.</b>	-30°C to 130°C
<b>Inside compound</b>	FKM/NBR
<b>Inside colour</b>	Black
<b>Reinforcement</b>	PVA
<b>Outside compound</b>	CSM
<b>Outside colour</b>	Black
<b>Standards</b>	SAE J30 R9 – 2022
<b>Std. branding</b>	

Inside dia. (mm)	Outside dia. (mm)	Working BAR	Burst Pressure BAR	Bend Radius (mm)	Weight (g/m)	Product code
4,8	11,8	10	62	46	195	3133048000
5,6	12,0	10	62	52	130	3133056000
6,0	12,0	10	62	55	140	3133060000
6,3	12,7	10	62	56	150	3133063000
7,3	13,3	7	62	60	165	3133073000
7,9	14,5	7	62	58	180	3133071000
9,5	16,5	7	62	62	230	3133095000
12,0	19,0	7	34	65	240	3133120000
12,7	19,9	7	34	68	250	3133127000
15,6	22,4	7	34	76	271	3133156000