



# 3135 Fuel Hose



## DESCRIPTION

Flexible, black hose for leaded and unleaded petrol Acc. to DIN 73379-1:1997. Good ozone resistance. Resistant to oil spray in engine compartments. For fuel pipes in cars, lorries, lawn mowers, garden cultivators, etc. Tolerances dimensions acc. DIN 1307, Available on plasticpolls in various lengths.

Please contact Codan for further information.

## ADDITIONAL INFORMATION

Type no.	3135
Application	Diesel, Fuel hose
Standard length	–
Working temp.	-30°C to 100°C
Inside compound	NBR
Inside colour	Black
Reinforcement	PVA
Outside compound	CR
Outside colour	Black
Standards	DIN 73379-1:2014
Std. branding	–

Inside dia. (mm)	Outside dia. (mm)	Working Pressure BAR	Burst Pressure BAR	Bend Radius (mm)	Weight (g/m)	Product code
3,0	9,0	10	30	38	80	3135030000
3,2	9,2	10	30	38	83	3135032000
3,5	9,5	10	30	38	85	3135035000
4,0	10,0	10	30	40	90	3135040000
4,5	10,5	10	30	43	94	3135045000
5,0	11,0	10	30	45	102	3135050000
5,3	11,3	10	30	46	108	3135053000
5,5	11,5	10	30	48	115	3135055000
6,0	12,0	10	30	50	120	3135060000
7,0	13,0	10	30	55	122	3135070000
7,3	13,3	10	30	60	124	3135073000
7,5	13,5	10	30	60	126	3135075000
8,0	14,0	10	30	63	154	3135080000
9,0	15,0	10	30	70	160	3135090000
9,3	15,3	10	30	70	165	3135093000
10,0	17,0	10	30	70	168	3135100000
11,3	18,3	10	30	75	122	3135113000
12,0	19,0	10	30	80	180	3135120000

This hose specification sheet has been prepared with great care in order to provide you with all the information you need. The written advice must be obtained from Codan Rubber before using any hose with untested media or before using in applications not covered in the product data sheet. Codan Rubber recommends regular maintenance, care, and inspection of hoses before use. Hoses should be replaced if any physical damage is seen, especially to the cover of the hose or in the area around the couplings. All products must be stored in accordance with ISO 2230:2002 (Storage of vulcanized Rubber Products).

The individual conditions of an application will affect the lifetime of each product. Therefore please ensure that resistance to chemicals and cleaning procedures in our written product information is complied with. Codan Rubber's warranty is void in the event of misuse such as excessive bending, crushing, stretching, use with incorrect media or use in environments outside the hose specification. Please contact Codan Rubber for individual product manufacturing tolerances.