



# 3201 Fuel Hose



## DESCRIPTION

Black hose for AdBlue, UREA, DEF, in and outside of peroxide cured EPDM for optimal resistance against AdBlue. Weather resistant peroxide EPDM (PER) cover. For use in AdBlue systems in automotive PV, trucks and buses. Manufactured based on DIN 73411/SAE J20.

For fitting assembly systems please contact Codan for further information here.

## ADDITIONAL INFORMATION

Type no.	3201
Application	AdBlue, Fuel hose
Standard length	50 metres
Working temp.	-40°C to 135°C
Inside compound	EPDM
Inside colour	Black
Reinforcement	Polyester
Outside compound	EPDM
Outside colour	Black
Standards	DIN 73411/SAE J20
Std. branding	–

Inside dia. (mm)	Outside dia. (mm)	Working BAR	Burst Pressure BAR	Bend Radius (mm)	Weight (g/m)	Product code
3,5	10,3	10	30	40	75	3201003000
4,0	11,0	10	30	40	85	3201004000
5,0	12,0	10	30	50	110	3201005000
6,0	13,0	10	30	50	130	3201006000
8,0	15,0	10	30	60	170	3201008000
10,0	17,0	10	30	70	210	3201010000

This hose specification sheet has been prepared with great care in order to provide you with all the information you need. The written advice must be obtained from Codan Rubber before using any hose with untested media or before using in applications not covered in the product data sheet. Codan Rubber recommends regular maintenance, care, and inspection of hoses before use. Hoses should be replaced if any physical damage is seen, especially to the cover of the hose or in the area around the couplings. All products must be stored in accordance with ISO 2230:2002 (Storage of vulcanized Rubber Products).

The individual conditions of an application will affect the lifetime of each product. Therefore please ensure that resistance to chemicals and cleaning procedures in our written product information is complied with. Codan Rubber's warranty is void in the event of misuse such as excessive bending, crushing, stretching, use with incorrect media or use in environments outside the hose specification. Please contact Codan Rubber for individual product manufacturing tolerances.