



3421 Fuel Hose



DESCRIPTION

Red, flexible hose with fabric reinforcement and conducting inner rubber coating.

For use on petrol pumps for all fuel types, including unleaded and diesel. Oil, weather and ozone-resistant CSM rubber ensures long service life and colour stability.

Fits standard, reusable petrol pump connectors.

Please contact Codan for further information.

ADDITIONAL INFORMATION

Type no.	3421
Application	Diesel / Pumps, Fuel hose
Standard length	50 metres
Working temp.	-30°C to 80°C
Inside compound	NBR
Inside colour	Black
Reinforcement	PVA
Outside compound	CSM
Outside colour	Red
Standards	–
Std. branding	–

Inside dia. (mm)	Outside dia. (mm)	Working Pressure BAR	Burst Pressure BAR	Bend Radius (mm)	Weight (g/m)	Product code
15,0	25,0	20	80	100	441	3421150000
15,9	25,9	20	80	110	458	3421159000
19,1	31,1	20	80	125	664	3421191000
25,1	38,4	20	80	150	913	3421254000

This hose specification sheet has been prepared with great care in order to provide you with all the information you need. The written advice must be obtained from Codan Rubber before using any hose with untested media or before using in applications not covered in the product data sheet. Codan Rubber recommends regular maintenance, care, and inspection of hoses before use. Hoses should be replaced if any physical damage is seen, especially to the cover of the hose or in the area around the couplings. All products must be stored in accordance with ISO 2230:2002 (Storage of vulcanized Rubber Products).

The individual conditions of an application will affect the lifetime of each product. Therefore please ensure that resistance to chemicals and cleaning procedures in our written product information is complied with. Codan Rubber's warranty is void in the event of misuse such as excessive bending, crushing, stretching, use with incorrect media or use in environments outside the hose specification. Please contact Codan Rubber for individual product manufacturing tolerances.