



4025 Brake Hose



DESCRIPTION

Black, wrapped hose with innerlayer made special for air with oilmoisture. Weather and ozone-resistant cover. Hose for use in air brake systems on trians. Complies UIC 830.1. Normally installed using specially designed claw couplings.

Please contact Codan for further information.

ADDITIONAL INFORMATION

Type no.	4025
Application	Compressed Air – Railway
Standard length	40 metres
Working temp.	-30°C to 70°C
Inside compound	NR
Inside colour	Black
Reinforcement	High Strength Synthetic Textile Yarns
Outside compound	CR
Outside colour	Black
Standards	UIC 830.1

Inside dia. (mm)	Outside dia. (mm)	Working Pressure BAR	Burst Pressure BAR	Bend Radius (mm)	Weight (g/m)	Product code
12,0	26,0	10	70	-	600	4025012000
16,0	30,0	10	70	-	750	4025016000
19,0	33,0	10	70	-	850	4025019000
22,0	36,0	10	70	-	1000	4025022000
28,0	47,0	10	70	-	1250	4025028000

This hose specification sheet has been prepared with great care in order to provide you with all the information you need. The written advice must be obtained from Codan Rubber before using any hose with untested media or before using in applications not covered in the product data sheet. Codan Rubber recommends regular maintenance, care, and inspection of hoses before use. Hoses should be replaced if any physical damage is seen, especially to the cover of the hose or in the area around the couplings. All products must be stored in accordance with ISO 2230:2002 (Storage of vulcanized Rubber Products).

The individual conditions of an application will affect the lifetime of each product. Therefore please ensure that resistance to chemicals and cleaning procedures in our written product information is complied with. Codan Rubber's warranty is void in the event of misuse such as excessive bending, crushing, stretching, use with incorrect media or use in environments outside the hose specification. Please contact Codan Rubber for individual product manufacturing tolerances.