



4411 Powersteering Hose



DESCRIPTION

Black High pressure power steering hose with wrapped cover and 2 layers of braided reinforcement. Low volume expansion, low noise transmission and high flexibility. Used in the automotive section both in the OEM and the Aftermarket. Used for the high pressure side of the powersteering system.

For the low pressure side please [click here](#).

ADDITIONAL INFORMATION

Type no.	4411
Application	Powersteering hose
Standard length	40 metres
Working temp.	-20°C to 125°C
Inside compound	NBR
Inside colour	Black
Reinforcement	PVA
Outside compound	CM
Outside colour	Black
Standards	SAE J 188: 2012

Inside dia. (mm)	Outside dia. (mm)	Working Pressure BAR	Burst Pressure BAR	Bend Radius (mm)	Weight (g/m)	Product code
9,5	19,7	105	500	75	308	4411095000

This hose specification sheet has been prepared with great care in order to provide you with all the information you need. The written advice must be obtained from Codan Rubber before using any hose with untested media or before using in applications not covered in the product data sheet. Codan Rubber recommends regular maintenance, care, and inspection of hoses before use. Hoses should be replaced if any physical damage is seen, especially to the cover of the hose or in the area around the couplings. All products must be stored in accordance with ISO 2230:2002 (Storage of vulcanized Rubber Products).

The individual conditions of an application will affect the lifetime of each product. Therefore please ensure that resistance to chemicals and cleaning procedures in our written product information is complied with. Codan Rubber's warranty is void in the event of misuse such as excessive bending, crushing, stretching, use with incorrect media or use in environments outside the hose specification. Please contact Codan Rubber for individual product manufacturing tolerances.