



# 4426 Powersteering Hose



## DESCRIPTION

Black Low pressure power steering hose with smooth cover. Low volume expansion, low noise transmission and high flexibility. Used in the automotive section both in the OEM and the Aftermarket. Used for the low pressure side of the powersteering system. For the high pressure side please [click here](#).

## ADDITIONAL INFORMATION

Type no.	4426
Application	Powersteering hose
Standard length	50 metres
Inside compound	NBR
Inside colour	Black
Reinforcement	PET
Outside compound	CM
Outside colour	Black
Standards	SAE J 189: 2012
Std. branding	—

Inside dia. (mm)	Outside dia. (mm)	Working Pressure BAR	Burst Pressure BAR	Bend Radius (mm)	Weight (g/m)	Product code
5,6	11,8	17	70	50	113	4426006
7,6	11,4	17	70	60	156	4426008
9,5	16,5	17	70	65	190	4426095
10,0	18,0	17	70	72	234	4426010
11,8	19,8	17	70	96	264	4426012
12,8	19,8	17	70	102	236	4426013
15,9	23,0	17	70	127	282	4426016

This hose specification sheet has been prepared with great care in order to provide you with all the information you need. The written advice must be obtained from Codan Rubber before using any hose with untested media or before using in applications not covered in the product data sheet. Codan Rubber recommends regular maintenance, care, and inspection of hoses before use. Hoses should be replaced if any physical damage is seen, especially to the cover of the hose or in the area around the couplings. All products must be stored in accordance with ISO 2230:2002 (Storage of vulcanized Rubber Products).

The individual conditions of an application will affect the lifetime of each product. Therefore please ensure that resistance to chemicals and cleaning procedures in our written product information is complied with. Codan Rubber's warranty is void in the event of misuse such as excessive bending, crushing, stretching, use with incorrect media or use in environments outside the hose specification. Please contact Codan Rubber for individual product manufacturing tolerances.