



4715 Oil Cooling Hose



DESCRIPTION

Black transmission oil cooling hose (TOC) with smooth cover and 1 layer of braided aramid reinforcement. AEM cover and liner together with the Aramid reinforcement withstands high temp applications, high flexibility and low volume expansion. Used in the automotive sector by the OEM's – Type A.

ADDITIONAL INFORMATION

Type no.	4715
Application	Oil Cooling hose
Standard length	50 metres
Working temp.	-40°C to 150°C
Inside compound	AEM
Inside colour	Black
Reinforcement	Aramid
Outside compound	AEM
Outside colour	Black
Standards	SAE J1532A: 2014
Std. branding	–

Inside dia. (mm)	Outside dia. (mm)	Working BAR	Burst Pressure BAR	Bend Radius (mm)	Weight (g/m)	Product code
7,5	14,5	20	50	72	153	4715007500
9,5	17,0	20	80	80	200	4715009500
11,0	18,5	20	80	88	219	4715011000
12,0	19,5	10	50	95	237	4715012000
18,5	27,0	10	50	133	384	4715018500
20,0	27,5	10	40	137	357	4715020000

This hose specification sheet has been prepared with great care in order to provide you with all the information you need. The written advice must be obtained from Codan Rubber before using any hose with untested media or before using in applications not covered in the product data sheet. Codan Rubber recommends regular maintenance, care, and inspection of hoses before use. Hoses should be replaced if any physical damage is seen, especially to the cover of the hose or in the area around the couplings. All products must be stored in accordance with ISO 2230:2002 (Storage of vulcanized Rubber Products).

The individual conditions of an application will affect the lifetime of each product. Therefore please ensure that resistance to chemicals and cleaning procedures in our written product information is complied with. Codan Rubber's warranty is void in the event of misuse such as excessive bending, crushing, stretching, use with incorrect media or use in environments outside the hose specification. Please contact Codan Rubber for individual product manufacturing tolerances.