



## DESCRIPTION

Black, flexible high-quality hose with low permeation, exceeding the industry standard of +80C-5kg/m<sup>2</sup>/year. This is due to a thin layer of PA build in the hose. inside a high quality EPDM.

For use in mobile and stationary refrigeration systems in which ONLY R134a is used.

Purpose-approved, crimped-on or reusable fittings are recommended. Also available in reduced dimensions see type nr. 5038.

Please contact Codan for further information.

## ADDITIONAL INFORMATION

<b>Type no.</b>	5035
<b>Application</b>	Air conditioning hose
<b>Standard length</b>	50 metres
<b>Working temp.</b>	-30°C to 100°C
<b>Inside compound</b>	EPDM
<b>Inside colour</b>	Black
<b>Reinforcement</b>	Polyester
<b>Outside compound</b>	EPDM
<b>Outside colour</b>	Black
<b>Standards</b>	SAE J2064:2011, Type C & SAE J3062: 2015
<b>Std. branding</b>	

Inside dia. (mm)	Outside dia. (mm)	Working Pressure BAR	Burst Pressure BAR	Bend Radius (mm)	Weight (g/m)	Product code
7.9	18.4	37	180	55	399	5035008000
10.3	22.4	37	180	65	559	5035010000
12.7	24.6	37	180	75	613	5035013000
15.9	28,6	20	180	90	721	5035016000
22.2	33.3	20	180	135	980	5035022000
28.5	39.7	20	180	180	1250	5035028000