



DESCRIPTION

Black, flexible high-quality smooth cover hose with low permeation, exceeding the industry standard for use with R134a/R1234yf, +80°C: Max.3kg/m²/year.

The inside tube is made with high quality IIR. Tested in: PAG(SP10, SP-A2, ND12)

For use in mobile and stationary refrigeration systems in which R134a and YF1234 is used.

Meets: SAEJ3062 C, ESDS7H-19B591_AA_rev_J, GMW14319

Please contact Codan for further information.

ADDITIONAL INFORMATION

Type no.	5039
Application	Air conditioning hose
Working temp.	-40°C to 125°C
Standard length	50 metres
Inside compound	Peroxide IIR/PA
Inside colour	Black
Reinforcement	Polyester
Outside compound	EPDM
Outside colour	Black
Standards	SAE J2064:2011, Type C & SAE J3062: 2015
Std. branding	

Inside dia. (mm)	Outside dia. (mm)	Working Pressure BAR	Burst Pressure BAR	Bend Radius (mm)	Weight (g/m)	Product code
8,2	14,8	35	180	55	140	5039008000
10,8	17,3	35	180	65	162	5039010000
13,1	19,4	35	180	75	186	5039013000
16,1	23,6	15	120	90	269	5039016000
19,4	27,4	15	120	130	344	5039019000