



8021 Food Hose



DESCRIPTION

Grey, smooth, flexible hose with BfR-approved inner rubber layer. For hot and cold beverages, e.g. beer, wine, fruit juice and milk.

Inner and outer surfaces resistant to vegetable and animal oils. Certification can be supplied.

It is recommended that new hoses are flushed with 5% soda solution before use. Flushing after use is also recommended.

Normally installed using stainless connectors or hose clamps.

Please contact Codan for further information.

ADDITIONAL INFORMATION

Type no.	8021
Application	Food / Beverages
Standard length	50 metres
Working temp.	-20°C to 100°C
Inside compound	NBR
Inside colour	White
Reinforcement	PVA
Outside compound	NBR/PVC
Outside colour	Grey
Standards	BfR, kap XXI, kat. 2. EU Reg. No.: 1935/2004 & 2023/2006
Std. branding	–

Inside dia. (mm)	Outside dia. (mm)	Working Pressure BAR	Burst Pressure BAR	Bend Radius (mm)	Weight (g/m)	Product code
6,3	15,0	20	60	60	203	8021006000
9,5	18,5	20	60	74	275	8021010000
12,7	21,6	20	60	86	333	8021013000
15,9	25,1	20	60	100	411	8021016000
19,1	28,6	20	60	114	490	8021019000
22,3	32,3	20	60	130	592	8021022000
25,4	35,6	20	60	142	673	8021025000

This hose specification sheet has been prepared with great care in order to provide you with all the information you need. The written advice must be obtained from Codan Rubber before using any hose with untested media or before using in applications not covered in the product data sheet. Codan Rubber recommends regular maintenance, care, and inspection of hoses before use. Hoses should be replaced if any physical damage is seen, especially to the cover of the hose or in the area around the couplings. All products must be stored in accordance with ISO 2230:2002 (Storage of vulcanized Rubber Products).

The individual conditions of an application will affect the lifetime of each product. Therefore please ensure that resistance to chemicals and cleaning procedures in our written product information is complied with. Codan Rubber's warranty is void in the event of misuse such as excessive bending, crushing, stretching, use with incorrect media or use in environments outside the hose specification. Please contact Codan Rubber for individual product manufacturing tolerances.