



# 8034 Food Hose



## DESCRIPTION

Red, wrapped suction/pressure hose with special compound outer coating which ensures that the hose is exceptionally hard-wearing and weather resistant. Double steel helix improves bend radius. Mainly for use in breweries as flexible connection between pipelines and tanks or tankers. Vacuum: 90%. Capable of withstanding brief periods of high temperature (120°C) during flushing/cleaning. Available in lengths of 40 m. Normally installed using stainless crimped-on fittings or hose clamps.

Please contact Codan for further information.

## ADDITIONAL INFORMATION

<b>Type no.</b>	8034
<b>Application</b>	Beer, Wine etc.
<b>Standard length</b>	40 metres
<b>Working temp.</b>	-40°C to 85°C
<b>Inside compound</b>	EPDM
<b>Inside colour</b>	White
<b>Reinforcement</b>	Polyester w/ double steel helix
<b>Outside compound</b>	EPDM
<b>Outside colour</b>	Red
<b>Standards</b>	FDA
<b>Std. branding</b>	-

Inside dia. (mm)	Outside dia. (mm)	Working Pressure BAR	Burst Pressure BAR	Bend Radius (mm)	Weight (g/m)	Product code
25,0	38,0	10	30	125	1060	8034025000
32,0	45,0	10	30	160	1300	8034032000
38,0	52,0	10	30	190	1620	8034038000
40,0	54,0	10	30	200	1680	8034040000
45,0	59,0	10	30	225	1880	8034045000
51,0	65,0	10	30	255	2140	8034051000
55,0	70,0	10	30	275	2330	8034055000
60,0	76,0	10	30	320	2700	8034060000
63,0	79,0	10	30	350	2940	8034063000
70,0	86,0	10	30	390	3250	8034070000
76,0	92,0	10	30	450	3480	8034076000
80,0	96,0	10	30	480	3700	8034080000
89,0	105,0	10	30	535	4040	8034089000
90,0	106,0	10	30	540	4090	8034090000
102,0	121,0	10	30	610	5560	8034102000

This hose specification sheet has been prepared with great care in order to provide you with all the information you need. The written advice must be obtained from Codan Rubber before using any hose with untested media or before using in applications not covered in the product data sheet. Codan Rubber recommends regular maintenance, care, and inspection of hoses before use. Hoses should be replaced if any physical damage is seen, especially to the cover of the hose or in the area around the couplings. All products must be stored in accordance with ISO 2230:2002 (Storage of vulcanized Rubber Products).

The individual conditions of an application will affect the lifetime of each product. Therefore please ensure that resistance to chemicals and cleaning procedures in our written product information is complied with. Codan Rubber's warranty is void in the event of misuse such as excessive bending, crushing, stretching, use with incorrect media or use in environments outside the hose specification. Please contact Codan Rubber for individual product manufacturing tolerances.