



<u> CODA</u>N 8040 FOOD HOSE - WP 10 BAR

## **DESCRIPTION**

A very hard-wearing suction/pressure hose. Food quality. Black wrapped look. Vacuum 70-99%.

Lengths: up to 4" - 40 m; 115 mm - 15 m; 127 and 152 mm - 25 m; 203 mm - 20 m.

## **ADDITIONAL INFORMATION**

Type no.	8040			
Application	ood quality – Material Handling			
Standard length	31 metres			
Working temp.	-35°C to 85°C			
Inside compound	NR			
Inside colour	White			
Reinforcement	Synthetic Textile yarns and 2 steel spirals			
Outside compound	SBR/NR			
Outside colour	Black			
Standards	-			
Std. branding	_			

Inside dia. (mm)	Outside dia. (mm)	Working Pressure BAR	Burst Pressure BAR	Bend Radius (mm)	Weight (g/m)	Product code
51,0	65,0	10	30	153	1500	8040051000
63,0	77,0	10	30	189	1830	8040063000
76,0	92,0	10	30	228	2810	8040076000
102,0	118,0	10	30	306	3730	8040102000
115,0	131,0	10	30	460	4200	8040115000
127,0	143,0	10	30	381	5130	8040127000
152,0	168,0	10	30	608	6010	8040152000
203,0	219,0	5	15	812	9000	8040203000

This hose specification sheet has been prepared with great care in order to provide you with all the information you need. The written advice must be obtained from Codan Rubber before using any hose with untested media or before using in applications not covered in the product data sheet. Codan Rubber recommends regular maintenance, care, and inspection of hoses before use. Hoses should be replaced if any physical damage is seen, especially to the cover of the hose or in the area around the couplings. All products must be stored in accordance with ISO 2230-2002 (Storage of vulcanized Rubber Products). The individual conditions of an application will affect the lifetime of each product. Therefore please ensure that resistance to chemicals and cleaning procedures in our written product information is complied with. Codan Rubber's warranty is void in the event of misuse such as excessive bending, crushing, stretching, use with incorrect media or use in environments outside the hose specification. Please contact Codan Rubber for individual product manufacturing tolerances.