




8512 Breathing Hose



DESCRIPTION

Black smooth cover. Medium pressure hose for respiratory equipment. Flame, heat and kink resistant. Antistatic properties. Fittings normally attached using a crimp ferrule.

Please contact Codan for further information.

ADDITIONAL INFORMATION

Type no.	8512
Application	Breathing hose
Standard length	50 metres
Working temp.	-50°C to 120°C
Inside compound	Breath quality NBR
Inside colour	Black
Reinforcement	PVA
Outside compound	CR
Outside colour	Black
Standards	EN 250: 2014
Std. branding	Codan 8512 Breathing hose WP 30 bar

Inside dia. (mm)	Outside dia. (mm)	Working Pressure BAR	Burst Pressure BAR	Bend Radius (mm)	Weight (g/m)	Product code
6,4	12,7	30	120	63	134	851200600
7,9	14,3	30	120	75	158	851200800

This hose specification sheet has been prepared with great care in order to provide you with all the information you need. The written advice must be obtained from Codan Rubber before using any hose with untested media or before using in applications not covered in the product data sheet. Codan Rubber recommends regular maintenance, care, and inspection of hoses before use. Hoses should be replaced if any physical damage is seen, especially to the cover of the hose or in the area around the couplings. All products must be stored in accordance with ISO 2230:2002 (Storage of vulcanized Rubber Products).

The individual conditions of an application will affect the lifetime of each product. Therefore please ensure that resistance to chemicals and cleaning procedures in our written product information is complied with. Codan Rubber's warranty is void in the event of misuse such as excessive bending, crushing, stretching, use with incorrect media or use in environments outside the hose specification. Please contact Codan Rubber for individual product manufacturing tolerances.