



8525 Breathing Hose



DESCRIPTION

White PVC antistatic pressure supply hose for medical gases. Mainly for use as flexible connection between equipment and wall supply points. DEHP Free. Braided hose reinforced with polyester yarns. Inner layer with semi-conductive compound, volumetric resistivity $<10^3 \text{ cm}$. Excellent resistance to static electricity.

Please contact Codan for further information.

ADDITIONAL INFORMATION

Type no.	8525
Application	Breathing hose
Standard length	20/50/100 metres
Working temp.	-10°C to 40°C
Inside compound	Semi-conductive compound
Inside colour	Black
Reinforcement	Polyester
Outside compound	TPE Compound free of Phtalates
Outside colour	White with black stripes
Standards	EN ISO 5359 / EN739
Std. branding	–

Inside dia. (mm)	Outside dia. (mm)	Working Pressure BAR	Burst Pressure BAR	Bend Radius (mm)	Weight (g/m)	Product code
6,7	12,7	20	60	40	120	8525006000

This hose specification sheet has been prepared with great care in order to provide you with all the information you need. The written advice must be obtained from Codan Rubber before using any hose with untested media or before using in applications not covered in the product data sheet. Codan Rubber recommends regular maintenance, care, and inspection of hoses before use. Hoses should be replaced if any physical damage is seen, especially to the cover of the hose or in the area around the couplings. All products must be stored in accordance with ISO 2230:2002 (Storage of vulcanized Rubber Products).

The individual conditions of an application will affect the lifetime of each product. Therefore please ensure that resistance to chemicals and cleaning procedures in our written product information is complied with. Codan Rubber's warranty is void in the event of misuse such as excessive bending, crushing, stretching, use with incorrect media or use in environments outside the hose specification. Please contact Codan Rubber for individual product manufacturing tolerances.