



Corrugated Breathing Hose



DESCRIPTION

Black, flexible, anti-static (ISO 2878:2011), corrugated, latex free, breathing tube.

For use with respiratory / diving / safety breathing apparatus, anaesthesia circuits, medical gas delivery.

Standard range shown include a flat 25mm cuff at each end.

These tubes can be made to customer specific dimensions on cuff size, wall thickness of rubber, corrugation size and length – a guide from 9.5mm ID to 50mm ID 90mm long to 2000mm long.

Tube corrugations can be compressed during production to add greater flexibility and kink resistance.

Please contact Codan for further details.

ADDITIONAL INFORMATION

Type no.	Corrugated breathing hose
Application	Breathing hose
Standard length	Variable length
Working temp.	-30°C to 110°C
Inside compound	EPDM
Inside colour	Black
Reinforcement	None
Outside compound	EPDM
Outside colour	Black
Standards	EN ISO 5367:2014 EU Dir 93/42/EEC amended 2007/47/EC Class IIa SMD
Std. branding	–

This hose specification sheet has been prepared with great care in order to provide you with all the information you need. The written advice must be obtained from Codan Rubber before using any hose with untested media or before using in applications not covered in the product data sheet. Codan Rubber recommends regular maintenance, care, and inspection of hoses before use. Hoses should be replaced if any physical damage is seen, especially to the cover of the hose or in the area around the couplings. All products must be stored in accordance with ISO 2230:2002 (Storage of vulcanized Rubber Products).

The individual conditions of an application will affect the lifetime of each product. Therefore please ensure that resistance to chemicals and cleaning procedures in our written product information is complied with. Codan Rubber's warranty is void in the event of misuse such as excessive bending, crushing, stretching, use with incorrect media or use in environments outside the hose specification. Please contact Codan Rubber for individual product manufacturing tolerances.